

6.5



FUNCTIONALLY DIVERSE. RUGGED PERFORMANCE.



Designed with law enforcement and rescue professionals in mind, the RIBCRAFT 6.5 provides excellent control and performance in confused and rough seas found along coast lines and high traffic waterways.

The pronounced bow sheer, full length lifting strakes, and RIBCRAFT deep V hull combine for unsurpassed handling. The 6.5's performance characteristics make it ideal for applications requiring speed and maneuverability. With ample deck space and a stable platform, the 6.5 is perfectly suited for diving operations. From rescue applications to routine patrols, at just over 21', the RIBCRAFT 6.5 offers multiple configurations and options suitable for any task at hand.

6.5 SPECS

LOA:	21'5"	INTERNAL LENGTH ON DECK:	16'4"
BEAM:	8'5"	INTERNAL BEAM ON DECK:	5'6"
WEIGHT (W/OUT ENGINE):	1,365 LBS	DRAFT (W/OUT ENGINE):	16"
DEAD RISE AFT:	25°	MAXIMUM PEOPLE:	12
DEAD RISE FORWARD:	44°	MAX HP:	180
TUBE DIAMETER:	20"		

6.5 STANDARD EQUIPMENT:

- Center console with front bench seat and grab handle
- Leaning post
- 60 gallon internal fuel tank
- Hydraulic steering with wheel
- 1670 dtx Hypalon® tube with five (5) chambers
- Pressure relief valves
- External lifelines
- Heavy duty rubstrake
- Stainless steel bow eye
- Anchor locker
- Stainless steel bow cleat
- Stainless steel transom tie down eyes
- Battery with retainer and switch
- Electrical panel
- Navigation lights
- Compass
- Electric bilge pump
- Molded non-skid deck






6.5 OPTIONAL EQUIPMENT: (PARTIAL LIST)

- Rescue console with attached pod seat with upholstered backrest and grab handle
- Windscreen
- Stainless steel console grab rail
- Pod seating with upholstered backrest and grab handle
- Two person bench seat with storage locker
- Aft bench seat
- Antenna arch
- Antenna arch with integrated dive ladder
- T-top
- Fore and aft tow posts
- Transom bollards
- Crash rail
- Stainless steel lifting points
- Keel guard
- Dive tank storage
- Reinforced tube at bow
- Boarding wear patches
- Tube grab handles
- Paddle/hook retainers
- Custom Hypalon® lettering
- Strobe and safety lights
- Electronics packages
- Complete engine packages
- Various hull and tube colors
- Marine grade aluminum hull

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, the 6.5 can be personalized to the mission.

All specifications, equipment, and options are subject to change without notice.

Specifications and Details

AF14 / AF16	4.8	5.7	5.85	6.5
				
LOA: 13'9" / 15'10"	LOA: 15'7"	LOA: 18'7"	LOA: 19'4"	LOA: 21'5"
Beam: 5'9" / 6'9"	Beam: 6'11"	Beam: 8'5"	Beam: 8'	Beam: 8'5"
Weight (w/out engine): 315 lbs / 390 lbs	Weight (w/out engine): 685 lbs	Weight (w/out engine): 1,890 lbs	Weight (w/out engine): 1,295 lbs	Weight (w/out engine): 1,365 lbs
Dead rise aft: N/A	Dead rise aft: 23°	Dead rise aft: 22°	Dead rise aft: 22°	Dead rise aft: 25°
Dead rise forward: N/A	Dead rise forward: 43°	Dead rise forward: 43°	Dead rise forward: 43°	Dead rise forward: 44°
Tube diameter: 20" / 20"	Tube diameter: 18"	Tube diameter: 20"	Tube diameter: 20"	Tube diameter: 20"
Internal length on deck: 10'2" / 11'6"	Internal length on deck: 11'10"	Internal length on deck: 13'10"	Internal length on deck: 14'9"	Internal length on deck: 16'4"
Internal beam on deck: 2'8" / 3'2"	Internal beam on deck: 4'1"	Internal beam on deck: 4'11"	Internal beam on deck: 5'1"	Internal beam on deck: 5'6"
Draft (w/out engine): 7" / 7"	Draft (w/out engine): 12"	Draft (w/out engine): 14"	Draft (w/out engine): 14"	Draft (w/out engine): 16"
Maximum people: 8 / 10	Maximum people: 6	Maximum people: 10	Maximum people: 10	Maximum people: 12
Max HP: 50 / 60	Max HP: 70	Max HP: 165	Max HP: 135	Max HP: 180
Fuel capacity: 6.6 gal*	Fuel capacity: 6.6 gal*	Fuel capacity: 33 gal	Fuel capacity: 46 gal	Fuel capacity: 60 gal
Tube: 1880 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®	Tube: 1670 dtx Hypalon®
Chambers: 4+2 / 5+2	Chambers: 5	Chambers: 5	Chambers: 5	Chambers: 5
Pressure relief valves: 4 / 5	Pressure relief valves: 5	Pressure relief valves: 5	Pressure relief valves: 5	Pressure relief valves: 5

*external tank

*external tank; optional internal 16 gal tank available

All specs, equipment and options subject to change without notice. | LOA and beam may vary slightly based on inflation pressure of the tube. | Additional dimensions/specs available on request.

Optional Equipment

Seating

Rescue console

Pod seat(s)

Two person bench seat

Full width aft bench seat

Three person bench seat with storage



Rescue Console



Pod seat(s)



Two person bench seat

Arches & Tops

Antenna arch

Antenna arch with dive ladder

T-top (not available on 4.8)

T-top courtesy upgrade

Folding bimini (4.8 & 5.85 only)



Antenna arch



Antenna arch with dive ladder



T-top

Accessories

Windscreen

Tow post (fore/aft)

Transom bollards

Engine crash rail

Lifting points

Keel guard

Aluminum beaching shoe


Dive tank storage



Engine crash rail



Tow post



Transom bollards

Tube Options

Reinforced tube at bow

Substrake reinforcing

Boarding wear patches

Tube grab handles

Paddle/hook retainers


Custom lettering



Reinforced tube at bow



Boarding wear patches



Tube grab handles

Various tube and hull colors include: Light Grey, Dark Grey, White, Blue, Cream, Black, Red, Yellow, Orange.
Electronics, lighting, and navigation packages available.

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, all models can be personalized to the mission.