

9.0 Offshore



UNMATCHED PERFORMANCE. HIGH CAPACITY. POWERFUL.



The workhorse of the RIBCRAFT line, the 9.0 is designed specifically for offshore rough water conditions.

A pronounced deep V hull coupled with full length lifting strakes, the 9.0 is designed specifically for rough water conditions that provides for unparalleled handling characteristics. Used by a variety of professionals from military and law enforcement agencies to tour operators and commercial organizations, the 29' RIBCRAFT 9.0 provides generous deck space for people and equipment. With numerous deck configurations available ranging from an open center console to multiple pod seats or a console enclosure, the RIBCRAFT 9.0 accommodates most applications.

9.0 SPECS

| | | | |
|------------------------|-----------|--------------------------|--------|
| LOA: | 29'7" | INTERNAL LENGTH ON DECK: | 22'10" |
| BEAM: | 10'3" | INTERNAL BEAM ON DECK: | 6'10" |
| WEIGHT (W/OUT ENGINE): | 3,395 LBS | DRAFT (W/OUT ENGINE): | 22" |
| DEAD RISE AFT: | 20° | MAXIMUM PEOPLE: | 20 |
| DEAD RISE FORWARD: | 40° | MAX HP: | 600 |
| TUBE DIAMETER: | 21" | | |

9.0 STANDARD EQUIPMENT:

- Center console with front bench seat and internal compartment
- Leaning post
- Bow storage locker
- 135 gallon internal fuel tank
- Hydraulic steering with wheel
- 1670 dtx Hypalon® tube with seven (7) chambers
- Pressure relief valves
- Stainless steel bow eye
- External lifelines
- Heavy duty rubstrake
- Stainless steel bow cleat
- Stainless steel transom tie down eyes
- Battery with retainer (2) and switch
- Electrical panel
- Navigation lights
- Compass
- Electric bilge pumps (3)






9.0 OPTIONAL EQUIPMENT: (PARTIAL LIST)

- Explorer console with single pod seat
- Windscreen
- Custom console enclosures
- Marine head
- Pod seating with upholstered backrest and grab handle
- Three person bench seat with storage locker
- Molded aft bench seat
- Suspension seating
- Antenna arch
- Antenna arch with integrated dive ladder
- T-top
- Adventure top with integrated dive ladder
- Fore and aft tow posts
- Transom bollards
- Crash rail
- Stainless steel lifting points
- Dive tank storage
- Keel guard
- Reinforced tube at bow
- Boarding wear patches
- Tube grab handles
- Paddle/hook retainers
- Strobe and safety lights
- Electronics packages
- Complete inboard and outboard engine packages
- USCG Certified Tour & Passenger-for-Hire packages
- Various hull and tube colors

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, the 9.0 can be personalized to the mission.

All specifications, equipment, and options are subject to change without notice.

Specifications and Details

| 6.8 | 7.0 | 7.8 | 9.0 | Express 32 |
|--|---|--|---|---|
|  |  |  |  |  |
| LOA: 22'5" | LOA: 24' | LOA: 25'7" | LOA: 29'7" | LOA: 32'3" |
| Beam: 8'8" | Beam: 8'8" | Beam: 8'9" | Beam: 10'3" | Beam: 10'3" |
| Weight (w/out engine): 2,275 lbs | Weight (w/out engine): 2,550 lbs | Weight (w/out engine): 2,670 lbs | Weight (w/out engine): 3,395 lbs | Weight (w/out engine): 7,000 lbs |
| Dead rise aft: 24° | Dead rise aft: 23° | Dead rise aft: 24° | Dead rise aft: 20° | Dead rise aft: 21° |
| Dead rise forward: 45° | Dead rise forward: 45° | Dead rise forward: 45° | Dead rise forward: 40° | Dead rise forward: 60° |
| Tube diameter: 20" | Tube diameter: 21" | Tube diameter: 20" | Tube diameter: 21" | Draft (engines down): 2'4" |
| Internal length on deck: 16'10" | Internal length on deck: 19'3" | Internal length on deck: 20' | Internal length on deck: 22'10" | Draft (engines up): 1'11" |
| Internal beam on deck: 5'10" | Internal beam on deck: 5'2" | Internal beam on deck: 5'10" | Internal beam on deck: 6'10" | Internal beam on deck: 5'6" |
| Draft (w/out engine): 18" | Draft (w/out engine): 15" | Draft (w/out engine): 18" | Draft (w/out engine): 22" | Water capacity: 35 gal |
| Maximum people: 12 | Maximum people: | Maximum people: 14 | Maximum people: 20 | Holding tank: 18 gal |
| Max HP: 230 | Max HP: 350 | Max HP: 300 | Max HP: 600 | Max HP: 700 |
| Fuel capacity: 80 gal | Fuel capacity: 70 gal | Fuel capacity: 100 gal | Fuel capacity: 135 gal | Fuel capacity: 180 gal |
| Tube: 1670 dtx Hypalon® | Tube: 1670 dtx Hypalon® | Tube: 1670 dtx Hypalon® | Tube: 1670 dtx Hypalon® | Tube: Hypalon® / Polyurethane |
| Chambers: 5 | Chambers: 7 | Chambers: 7 | Chambers: 7 | Chambers: 7 |
| Pressure relief valves: 5 | Pressure relief valves: 7 | Pressure relief valves: 7 | Pressure relief valves: 7 | Pressure relief valves: 7 |

All specs, equipment and options subject to change without notice. | LOA and beam may vary slightly based on inflation pressure of the tube. | Additional dimensions/specs available on request.

Optional Equipment

Seating

Explorer console

Pod seat(s)

Aft molded bench seat

Centerline back to back bench seat

Full width aft bench seat

Suspension seating



Explorer console



Pod seat(s)



Full width aft bench seat

Arches & Tops

Antenna arch

Antenna arch with dive ladder

T-top

T-top courtesy upgrade

Aluminum top upgrade

Adventure top



Antenna arch



Antenna arch with dive ladder



T-top

Accessories

Windscreen

Tow post (fore/aft)

Transom bollards

Engine crash rail

Lifting points

Keel guard

Aluminum beaching shoe

Dive tank storage



Engine crash rail



Tow post



Transom bollards

Tube Options

Reinforced tube at bow

Rubstrake reinforcing

Boarding wear patches

Tube grab handles

Paddle/hook retainers

Custom lettering



Reinforced tube at bow



Boarding wear patches



Tube grab handles

Various tube and hull colors include: Light Grey, Dark Grey, White, Blue, Cream, Black, Red, Yellow, Orange. Electronics, lighting, and navigation packages available.

With accessory choices, console and seating configurations, propulsion options, and a variety of navigation and communication equipment, all models can be personalized to the mission.